



## Declaration of Performance

In accordance with the CPR Regulation (EU) N° 305/2011

Reference nr: 230866

Unique identification code of the product-type

**Soudaflex 20LM**

Intended use or uses of the construction product

**Sealants for facade for interior and exterior application  
Sealants for pedestrian walkways for interior use**

Name and contact address of the manufacturer as required pursuant to Article 11(5)

**Soudal NV, Everdongenlaan 18-20, 2300 Turnhout, Belgium**

System(s) of assessment and verification of consistency of performance of the construction product, as set out in Annex V

**System 3: for reaction to fire  
System 3: for essential characteristics**

Construction product in accordance with applicable harmonised specifications

**EN 15651-1:2012: Type F-EXT-INT 25LM  
EN 15651-4:2012: Type PW-INT**

The notified body

**The notified body GINGER CEBTP, NB 0074 has carried out Determination of Product Type under system 3.**

**Declared Performance: EN 15651-1:2012**

Essential Characteristics	Performance	Harmonised Technical Specification
Reaction to fire	E	EN 15651-1:2012
Release dangerous chemicals	NPD	
Water and air tightness		
Resistance to flow	≤ 3 mm	
Loss of volume	≤ 10%	
Tensile properties at maintained extension after water immersion	NF	
Durability	Pass	

**Conditioning:** Method A

**Test Substrate:** aluminium, mortar

**Declared Performance: EN 15651-4:2012**

Essential Characteristics	Performance	Harmonised Technical Specification
Reaction to fire	E	EN 15651-4:2012
Release dangerous chemicals	NPD	
Water and air tightness		
Loss of volume	≤ 10%	
Tensile properties at maintained extension	NF	
Tear resistance	NF	
Durability	Pass	

**Conditioning:** Method A

**Test Substrate:** aluminium, mortar

The performance of this product is in conformity with the declared performance. This declaration of performance is issued under the sole responsibility of the manufacturer.

Signed for on behalf of the manufacturer by



Ing. W. Dierckx  
Senior Technical Product Manager  
Soudal NV- Belgium

## CE marking

In accordance with the CPR Regulation (EU) N° 305/2011



NB 0074

Soudal NV, Everdongenlaan 18-20, 2300 Turnhout, Belgium

14

Reference nr: 230866

EN 15651-1:2012

EN 15651-4:2012

Sealants for facade for interior and exterior application

Sealants for pedestrian walkways for interior use

### Soudaflex 20LM

EN 15651-1:2012: Type F-EXT-INT 25LM

EN 15651-4:2012: Type PW-INT

**Conditioning:** Method A

**Test Substrate:** aluminium, mortar

Essential Characteristics	Performance	Harmonised Technical Specification
Reaction to fire	E	EN 15651-1:2012 EN 15651-4:2012
Release dangerous chemicals	NPD	
Water and air tightness		
Resistance to flow	≤ 3 mm	
Loss of volume	≤ 10%	
Tensile properties at maintained extension after water immersion	NF	
Tensile properties at maintained extension	NF	
Tear resistance	NF	
Durability	Pass	